

Cradle Reel Elevators

Part No. CVC002



Options

- ▶ Disk brake device CDF007
- ▶ (Max torque 1.3kN-m)

- ✓ Detachable frame
- ✓ Light design

Reel model	Dimensions (mm)	Capacity (kN)	Wt (kg)
BOF010/ BOF020	2550L x 1325W x 1060H	20	58

Drum Stand - 3T

Part No. ME-DS-3.0T



- ✓ 350 Grade Steel Plate and RHS Hot Dip Galvanised
- ✓ Designed for independent payout tension of cable

Drum Qty & Capacity (mm)	Spindle Shaft Size (mm)
1 Drum up to 2600 Dia. x 1500 wide	80

Load rating per spindle (T)	Line Pull
3	500kg at 1000mm Dia.

Square collars available to suit 105mm spindle cut out on Rail Industry drums

Cable Drum Stand

Part No. DSF Series

Cable drum "A" frame stand with spindle and spindle accessories



Model	WLL (T)	Max Width (mm)	Max Diameter (mm)
DSF2016-6T	6	2000	1600
DSF2420-12T	12	2400	2000
DSF3624-16T	16	3600	2400

Model	Options		
	Brake	Drum Fixing Arm	Levelling Screws
DSF2016-6T	Yes	Yes	Yes
DSF2420-12T	Yes	Yes	Yes
DSF3624-16T	Yes	Yes	No